

Closed injection moulded closure

The present invention relates to a closed injection moulded closure according to the precharacterizing
5 clause of independent Patent Claim 1.

Int 017

The prior art discloses various plastics closures having snap-on hinges. To enable them to function, they must for technical reasons generally be produced
10 in the open position. For cost reasons, however, attempts have been made to injection mould such closures in the closed state, especially to reduce the mould cost and the production costs, inter alia with avoidance of the so-called covering process.

15 Closed injection moulded closures are accordingly advantageous as they are cheaper, permit a simpler mould and furthermore offer the opportunity of integrating an original warranty seal without substantial additional cost. Examples of suitable
20 original warranty seals are tear-off lips or weak points in the form of thin connecting webs. These tear-off lips or thin areas must be removed or deliberately destroyed on opening for the first time. Particularly in the case of foods, medicaments or
25 products for infants, product safety is having to meet increasing legal requirements, which further increases the interest in corresponding closures having original warranty seals.

30 The prior art discloses individual one-part closed injection moulded closures which however are not convincing in their mode of operation. Mainly owing to too small an opening angle, a poor snap-on effect

and inadequate design as well as insufficient sealing, these closures have not become established on the market. In the opened position, the movable closure part is in such an unfavourable position that

5 it constantly and unavoidably comes into contact with the contents and thus becomes soiled. Moreover, this closure part is so close to the pouring opening that it blocks said opening visually. From the point of view of injection moulding too, these closures are

10 not without problems. Asymmetrical flow paths, an unfavourable arrangement of the film hinges and cooling problems are only a few of the problems. Owing to the system itself, these disadvantages cannot be overcome. In particular, the main hinge

15 connections between the closure parts, which force the closure parts to form a rotational movement and limit the kinematics of closure are troublesome and particularly disadvantageous.

20 For example, EP 0 532 471 describes a closure which has the disadvantages described above. The lower closure part is connected to the movable upper closure part by means of a main hinge connection and two laterally arranged tension bands. The hinge

25 connections and the tension bands must be arranged in such a way that they are on the one hand capable of being removed from the mould and are accessible from both sides (outside and inside). The unavoidable main hinge connection results in the closure parts having

30 to be arranged very close together, with the correspondingly adverse effect on the opened state. The accessibility of the hinge region, which is essential for production, moreover means that the

Jas
027

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2

305
03 7

5 tension bands cannot be designed in any desired manner and the angle between open and closed positions remains in the region of 80° or less. In addition, the upper closure part in the open position is in a poor, unstable and random arrangement relative to the spout. An insufficient snap-on effect and the absolutely unfavourable position of the upper closure part relative to the lower closure part in the opened position are obstacles to effective

10 operation. Problems with the flow paths and poor design are further weaknesses. The main hinge connection moreover results in the closure parts moving along circular paths and therefore being subject to considerable restrictions with regard to

15 the spatial arrangement.

The disadvantages described above cannot be overcome by means of the conventional closures which are known from the prior art.

20 It is therefore an object of the present invention to provide a closed injection moulded closure which does not have the disadvantages known from the prior art and which has a large, adjustable opening angle and a

25 substantial snap-on effect. It is also an object of the present invention to provide a closure in which the movable closure part in the open position can be arranged so that it is away from the mouth region of the spout. In addition, the closure should, if

30 desired, offer the possibility of being child-proof and secure during transport and should provide a good seal even in the case of contents with gas pressure.

IAS 94 >
This object is achieved by the invention defined in the Patent Claims.

The invention disclosed here avoids in advance the
5 bottlenecks to which constructions according to the
prior art are subject, by deliberately avoiding a
main hinge connection between the closure parts. The
movable closure part is positioned outside the zone
of the spout or opening. Consequently, soiling of the
10 movable closure part by the contents and visual and
functional blocking are prevented. The snap-on effect
is established and predetermined in a specific manner
in line with the requirements. Owing to the absence
of a main hinge, it is also possible for the first
15 time to realize substantially symmetrical flow paths
in the hinge region in the case of closed injection
moulded closures. As a result of this, problems such
as material backflow and cold welds do not occur.

20 Because the connection lacks a main hinge, it is
furthermore achieved that the closure parts no longer
move along circular paths relative to one another.
The spatial trajectories instead correspond to
adjustable movement paths which are adapted to the
25 respective requirements. High spouts and other
obstacles are overcome in a specific manner. The
invention envisages that closed injection moulded
closures can be produced with avoidance of the known
disadvantages, with or without original warranty
30 seals and with a good design. If desired in a
specific case, child-proof properties and security
during transport as well as particular sealing in the
case of contents with gas pressure can be provided.

Embodiments of the invention are explained in more detail with reference to the following Figures:

5 Figure 1 schematically shows a closure according to the prior art;

Figure 2 schematically shows a closure according to the invention disclosed here;

10

Figure 3 shows a preferred embodiment of a closure according to the invention;

15

Figure 4 shows a closure according to Figure 3, in the open position;

Figure 5 shows a closed injection moulded closure with hinge connection arranged at the top.

20 Figure 1 shows a schematic side view of a closed injection moulded closure 1, as known from the prior art. A lower closure part 2 and a movable upper closure part 3 can be seen. The upper closure part 3 is connected to the lower closure part 2 by means of a conventional snap-on hinge 4. The snap-on hinge 4 consists of a main hinge connection 5 and two tension bands 6.1 and 6.2 (because of the direction of view, only the tension band 6.1 is visible here) which each connect the lower closure part 2 to the upper closure
25 part 3 and as a rule are arranged by the side of the main hinge connection 5. Instead of tension bands 6.1, 6.2, there are also other known elements, such as toggle levers, etc., which are not used in
30

practice in closed injection moulded closures owing to various disadvantages. The main hinge connection 5 forms a direct hinge connection with only one hinge axis between the lower closure part 2 and the upper closure part 3. This hinge axis of the main hinge connection 5 is parallel to the direction of view in the representation shown here. Owing to the main hinge connection 5 having a hinge axis, all parts rotate relative to one another along circular paths.

10 In order to be able to produce the closure 1 in the closed position of the upper closure part 3, the main hinge connection 5 and tension bands 6.1, 6.2 and in particular their connections to the closure parts 2 and 3 must be arranged in such a way that they are

15 accessible in the injection mould (not shown) from the inside of the closure (arrow 10) and from the outside of the closure (arrow 11). Particularly the main hinge is difficult to form. Owing to these facts, the function (snap-on effect) and the

20 arrangement (open position) of the upper closure part in the case of the closures known from the prior art are very restricted and inadequate. A typical open position of the upper closure part 3 is represented by an upper closure part 7. The open position of the

25 tension bands 6 is represented by tension bands 8.1, 8.2 (only one can be seen). Owing to the unavoidable main hinge connection 5 in this closure concept, the closure 1 shown here has a small opening angle of about 80° and a poor snap-on effect.

30

~~Figure 2 schematically shows a closed injection moulded closure 20 according to the invention disclosed here. The closure 20 consists of a lower~~

30
Inc B

A
B

closure part 21 and an upper closure part 22, which is shown here in the closed position in which it is also produced. According to the invention, the closure 20 shown here has (in contrast to the prior art) no main hinge connection (cf. Figure 1) between the closure parts 21 and 22. The closure parts 21 and 22 are instead actively connected to one another by two, preferably symmetrically formed, elements 23.1 and 23.2 (owing to the direction of view, only one element 23.1 is visible) and four hinge connections 24.1, 24.2, 25.1 and 25.2. Two hinge connections 24.1, 25.1 and 24.2, 25.2 each border an element 23.1 and 23.2, respectively, on non-adjacent sides and connect it to the closure parts 21 and 22, respectively. The hinge connections 24.1 and 25.1, and 24.2 and 25.2, respectively, make an angle ϕ (cf. also Figure 3) with one another. The two planes defined by the hinge connections 24.1 and 25.1, and 24.2 and 25.2, respectively (not shown) in turn make an angle ω . By varying the angles ω and ϕ and their ratio to one another, the snap-on effect and an opening angle α of the closure are determined. The relationship between the opening angle α and the angles ω and ϕ is given by the following formula:

$$\phi = 2 \cdot \arctan \left[\frac{\sin(\alpha / 2)}{1 - \cos(\alpha / 2)} \cdot \sin(\omega / 2) \right]$$

To be able to produce the closure 20 in the closed position, the elements 23.1 and 23.2 and the hinge connections 24.1, 24.2, 25.1 and 25.2 are arranged in such a way that they are accessible in the mould from the inside of the closure (arrow 27) and from the

~~outside of the closure (arrow 28) and can be removed~~
from the mould. For this purpose, the connecting
elements 23.1, 23.2 and the associated hinge
connections are arranged in a surface which is
5 inclined relative to the closure axis. Preferably,
hinges according to the patents EP 0 746 512,
PCT/EP96/2780 or the Patent Application
PCT/1999/00277 of the same Applicant are used for the
closure, the contents of which are hereby
10 incorporated by reference with regard to the details
of the design of the hinges. Particularly in the case
of closures having curved contours in which the
connecting elements 23.1, 23.3 have a corresponding
convexity or curvature owing to their contour
15 integration, the hinge according to PCT/EP96/2780 is
advantageous since the elastic strain of the long
edge 46 (cf. Figure 3) under tension has the desired
~~snap-on effect~~

~~A typical open position of the upper closure part 22~~
is represented by an upper closure part 29. The
corresponding open positions of the element 23.1 or
23.2 and of the hinge connection 25.1 or 25.2 are
represented by an element 30.1 or 30.2 and a hinge
25 connection 31.1 or 31.2. By avoiding a main hinge
connection between the closure parts 21 and 22, it is
possible to arrange the upper closure part 22 in its
open position (upper closure part 29) in such a way
that an optimal and, if required, predeterminable
30 opening angle and an adjustable snap-on effect
result. The predetermined opening angle is preferably
in the range from 150° to 180° but may also be
adapted to other requirements. On comparison of the

~~closures shown in Figure 1 (prior art) and Figure 2~~
(invention), the surprising importance of the
invention disclosed here for closures produced in the
closed state will become clear to the person skilled
5 ~~in the art.~~

Ins D7
A Figure 3 shows an embodiment of a closure 20
according to the invention in a perspective view. A
lower closure part 21 and an upper closure part 22
10 can be seen. These are connected to one another by
means of two elements 23.1 and 23.2 and four hinge
connections 24.1, 24.2 and 25.1, 25.2, respectively,
which border said elements. The hinge connections
24.1 and 25.1, and 24.2 and 25.2, respectively, each
15 together define a plane 31 or 32, respectively, and
make an angle ϕ with one another. The edges 45 closer
to the apex of the angle ϕ are preferably
substantially pressure-resistant. The planes 31 and
32 in turn make a solid angle ω with one another. The
20 planes 31 and 32 are inclined relative to the closure
axis in such a way that they are further away from
the closure axis in the region of the lower
connection (lower closure part 21) than in the region
of the upper connection (upper closure part 22). This
25 permits demouldability of the closure while also
making it possible to form the desired hinge. In the
embodiment shown, the connecting elements 23.1, 23.2
are integrated into a convex outer contour of the
closure, with a correspondingly acute angle ω
30 ($< 180^\circ$) between the planes 31 and 32. In other
embodiments having a concave outer contour, an obtuse
angle ($> 180^\circ$) is enclosed between the two planes 31,
32. The hinge connections 24.1, 24.2 and 25.1, 25.2

are preferably film hinges as known from the prior art. The desired bending ranges can however also be different. In the closed position shown here, the closure 20 is preferably produced by means of injection moulding. The closure parts 21, 22 and 23.1, 23.2 and the hinge connections 24.1, 24.2, 25.1, 25.2 are functionally separated from one another here by all-round gaps 33 to 38 so that the movable upper closure part 22 can assume at least two spatially defined and stable positions relative to the lower closure part 21. There are unstable states (dead points) between these stable positions so that the upper closure part 22 automatically attempts to achieve the nearest stable position and hence has a snap-on effect. In certain stable positions, in particular in the closed position of the closure 20 shown here, the closure parts 21, 22, 23.1, 23.2, 24.1, 24.2, 25.1, 25.2 are in substantially stress-free states (geometric deformations). In addition to these stress-free, stable positions, non-stress-free stable positions are also possible. In these positions, the elements 23.1 and 23.2 and the hinge connections 24.1, 24.2, 25.1, 25.2 are typically under a torsional stress and the secondary stresses caused thereby. The elements 23.1 and 23.2 are formed along a shorter free edge 45.1 or 45.2 in such a way that they do not buckle under the pressures occurring. The longer free edges 46.1 and 46.2 are preferably designed in such a way that they lengthen elastically and reversibly under the tensile stresses occurring. This can be achieved, for example, by a three-dimensional curvature or specific choice of material. The closure parts 21 and 22 advantageously

~~have a certain elasticity so that, if required, they~~
undergo reversible elastic deformation under the
loads occurring. The elements 23.1 and 23.2 are
advantageously formed in such a way that they deform
5 in a controlled manner owing to the torsional forces
occurring. The coordination between the closure parts
21 and 22 is adjustable through the torsional
rigidity of the elements 23.1, 23.2. The desired
snap-on effect can thus be achieved by the closure
10 parts or by the connecting elements individually or
in combination with one another. Owing to the low
torsional rigidity of the elements 23.1 and 23.2, it
is possible to achieve intermediate states in which
the closure parts are stable relative to one another
15 but do not assume tension-free positions. Closures
having a plurality of open positions can thus be
realized.

Ins Dg
20 ~~The closure parts are separated from one another by~~
the gaps 33 to 38 so that the closure 20 can be
opened and closed. The gaps 33 to 38 are formed in
such a way that they are optimally accessible in the
mould and can be removed from the mould. Elements 39
are present in the gap 33 of the embodiment shown
25 here. Said elements additionally connect the closure
parts 21 and 22. The elements 39 are designed in such
a way that, if required, they serve as predetermined
breaking points which are destroyed when the closure
is first opened. The elements 39 may also be in the
30 form of all-round, membrane-like predetermined
breaking points which enclose one or more desired
sectors. A consumer can thus recognize whether the
closure has already been opened before purchase

(original warranty seal). The elements 39 also serve for preventing unintentional opening during transport, since a greater force has to be overcome on opening for the first time. In addition to the above-mentioned points, the elements 39 also serve as flow aids in the production of the closure 20, in order to achieve better filling of the mould. Instead of elements 39, other equivalent means (not shown) are also possible, for example in the form of tear-off lips, which have to be removed before opening for the first time, for example by tearing off. Integrations of further functions are not hindered. The course of the gaps 33 to 38 can be substantially freely chosen provided that there is no impairment of the mode of operation of the closure and the producibility. The elements 23.1 and 23.2 are preferably integrated into the outer contour of the closure parts 21 and 22. In the invention disclosed here, the design is subject to few limits, in contrast to the prior art. Here, the elements 23.1 and 23.2 are adapted to the outer contour of the closure and are integrated therein. Of course, they may also have another design or may be flat. If required, they may have a connection to one another. An advantageous connection can be realized, for example, in the form of a further (straight) hinged connection, in the form of a film hinge in the case of plastics.

Ins Dg 1
30 ~~Figure 4 shows the closure 20 according to Figure 3 in the opened position, in a perspective sectional view. Here, the closure 20 is pressed onto a bottle 50 and thereby fastened. Here, the upper closure part~~

22 ~~is present in a stable open position swivelled~~
180° backwards so that a pouring opening 51 for
pouring out the content contained in the bottle 50 is
unobstructed. In the embodiment shown here, upper
5 closure part 22 is present in an oblique position
above the lower closure part 21 so that it does not
hinder pouring and the spout 51 is visually not
concealed. Because the main hinge connection has been
avoided according to the invention and owing to the
10 length of the connecting elements 23.1, 23.2, it is
possible to bring the upper closure part 22 into this
position in a closed injection moulded closure 20. In
the case of the closures known from the prior art, an
upper closure part generally hinders pouring. The
15 elements 39 were destroyed here on deliberately
opening the closure 20. Residues of the elements 39
are therefore present both on the lower closure part
21 and on the upper closure part 22. It is thus
safely indicated to a user that the closure 20 was
20 opened at least once. The closure parts 21, 22, 23.1,
23.2, 24.1, 24.2, 25.1, 25.2 are advantageously
substantially tension-free in the open position of
the closure 20 shown here. This means that the
closure parts 21, 22, 23.1, 23.2 (except for the
25 hinge connections 24.1, 24.2, 25.1, 25.2) are not
subject to any deformations. In the interior of the
closure 23, preferably in the region of the elements
23.1 and 23.2, means 52 for partial stiffening of the
closure parts 21, 22, 23.1, 23.2 are present on the
30 closure parts 21, 22, 23.1, 23.2. The snap-on
behaviour and the functionality of the closure 20 are
thus influenced in a controlled manner. Means 52 used
for stiffening the closure parts are preferably ribs,

thicker regions or other, equivalent means.

Ins Dio

^
A tubular element 53 which in this case has an edge 55 thickened by means of a bead 54 is evident in the interior of the upper closure part 22. The element 53 or the bead 54 corresponds, in a closed position of the closure 20, to the spout 51 of the bottle 50 or of an adapter between bottle and closure so that said bottle is sealed. The element 53, the bead 54 and the spout 51 actively connected to them in the closed position of the closure 20 are advantageously designed in such a way that the sealing effect is adjusted proportionally to the internal pressure of the bottle 50. This can be achieved, for example, through the geometry of the tubular element 53 if the edge 55 or the bead 54 expands proportionally to the internal pressure and to a greater extent than the increase in the diameter of the spout 51. Consequently, the edge 55 is pressed to a greater extent against the inner wall 56 of the spout 51 with increasing internal pressure, with the result that the sealing effect is enhanced. Active element 57 is present on the inside of the upper closure part 22. In the closed position of the closure 20, this active element 57 has an active connection to a counter-element, in this case an outer edge 58 of the bottle 50, by virtue of the fact that it grips under said counter-element and thus prevents unintentional opening of the closure 20, for example during transportation or in the case of high internal pressures. This locking mechanism can be temporarily released here by lateral pressure on the upper closure part 22 in the direction of the arrows 59 and

60. As a result of the lateral pressure, the upper closure part is deformed in such a way that the catch 57 moves in the direction of an arrow 61 and the active connection with the outer edge 58 is temporarily broken. The closure 20 can thus be opened. The locking mechanism shown here is also particularly suitable for combination with a quality seal or original warranty seal in the form of a tear-off lip (not shown). Of course, it is also possible to use more than one catch 57 or to position said catch otherwise. The effective ranges of the pressures must be appropriately adjusted. Thus, the closure according to the invention can be used even in the case of high internal pressures.

15

Ins Dn A Figure 5 shows another embodiment of a closure 1 which is mounted on, preferably forced onto, a container 12. The closure comprises a first, fixed closure part 62 and a second, movable closure part 63. The container 12 may have, in the region of its upper end 67, a complete opening which substantially extends over its total cross-section, or, in the region of the movable closure part 63, by a smaller opening which appears as soon as the movable closure part 63 opens. Arranged in the region of the transition 68 between the two closure parts are two connecting elements 23.1, 23.2, which form the hinge connection between the two closure parts. In contrast to the closures described above, the connecting elements are arranged not by the side of the closure in an inclined surface but on the top of the closure (relative to the closure axis). The geometry of the two connecting elements 23.1, 23.2 is preferably

designed so that the movable closure part performs a snap-on movement of about 90° or 180° , the formula mentioned above in association with Figure 2 being used to obtain the desired opening angle α . Of course, it is also possible to obtain other intermediate angles by corresponding modification of the hinge connections 24.1, 25.1 and 24.2, 25.2. The avoidance, according to the invention, of a main hinge in combination with the mutual arrangement of the closure parts permits such a closure having a large opening angle α .

The external geometry of the closure can have a convex shape, as shown here. However, closures in which the connecting elements are arranged in a depression or in which the external geometry is substantially concave can also be realized. The arrangement of the hinge connections in the upper region of the closure permits particularly advantageous hinges and predetermined breaking points for achieving an original warranty seal if, for example, the transition 68 between the two closure parts 62, 63 is not continuously separated but contains connections or connecting regions which have predetermined breaking points and are parted only on opening for the first time. According to the invention, it is possible to integrate the connecting elements 23.1, 23.2 completely into the closure contour so that a large number of closure designs are possible. For example, the movable closure part can be made smaller and can be surrounded by the fixed closure part so that, as a result of opening the movable closure part, an opening in the closure

